

20 JUN 2005

Ministry of Economic  
Development

Manatū Ōhanga

Intellectual Property Office  
of New Zealand

PCT/NZ03/00292

REC'D 21 JAN 2004

WIPO

PCT

## CERTIFICATE

This certificate is issued in support of an application for Patent registration in a country outside New Zealand pursuant to the Patents Act 1953 and the Regulations thereunder.

I hereby certify that annexed is a true copy of the Provisional Specification as filed on 20 December 2002 with an application for Letters Patent number 523369 made by SENSORTEC LIMITED.

Dated 9 January 2004.

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)



Neville Harris  
Commissioner of Patents, Trade Marks and Designs



**BEST AVAILABLE COPY**

Intellectual Property  
Office of NZ

20 DEC 2002

RECEIVED

**PATENTS FORM NO. 4**

Appln Fee: \$50.00

James & Wells ref: 121502/28 JW

**PATENTS ACT 1953**

**PROVISIONAL SPECIFICATION**

**MILK PROCESSING**

I/WE      SENSORTEC LIMITED a New Zealand company of 558 Te Rapa Road,  
Hamilton, New Zealand

do hereby declare this invention to be described in the following statement:

## MILK PROCESSING

### TECHNICAL FIELD

This invention relates to a method of milk processing. Specifically, this invention relates to the on farm separation of milk components.

### 5 BACKGROUND ART

In New Zealand, most dairy animals such as cows are generally milked twice daily, the milk being collected into a main storage vat before being transported in bulk to a milk treatment station.

10 The milk is then processed into a range of products, including pasteurised milk, powdered milk, butter, cheese or milk derivatives.

The production of butter and cheese results in large volumes of by-products such as whey which can be further processed on-site or transported to another specialist treatment station. A number of components can be fractionated from such milk by-products including carbohydrates, whey protein bioactives such as lactoferrin and so  
15 forth.

However, the standard processing of milk and milk by-products thus results in high transport and handling costs associated with processing such large volumes of milk.

Further, due to the time delay between the collection of milk on farm and its subsequent processing off site, milk proteins such as bioactives may be subjected to  
20 proteolytic degradation by enzymes such as proteases, or may be inactivated or lose activity through a number of other interactions.

The act of transporting and processing the milk may also denature a number of bioactive proteins through the physical handling or heating of the liquid.

To attempt to overcome some of these problems, NZ280724 disclosed a process for the isolation of endogenous milk proteins by on farm processing of milk using standard separation techniques such as chromatographic resins.

5 Such processes were useful in the separation of bioactive proteins in the minimum amount of time, ensuring minimal degradation or loss of activity of the bioactive proteins.

However, while these methods work well in an experimental situation, the volume of milk collected during a standard milking often meant such standard separation techniques were not optimal.

10 Chromatographic resins are primarily designed to process small volumes of liquid, usually at low flow rates to ensure good component separation. Increasing the flow rate not only reduces the degree of separation but may damage the resin or chromatographic column. As large amounts of resin would be required to cope with normal milking volumes without overloading, these techniques may be prohibitively  
15 expensive.

All references, including any patents or patent applications cited in this specification are hereby incorporated by reference. No admission is made that any reference constitutes prior art. The discussion of the references states what their authors assert, and the applicants reserve the right to challenge the accuracy and pertinency of the  
20 cited documents. It will be clearly understood that, although a number of prior art publications are referred to herein, this reference does not constitute an admission that any of these documents form part of the common general knowledge in the art, in New Zealand or in any other country.

It is acknowledged that the term 'comprise' may, under varying jurisdictions, be  
25 attributed with either an exclusive or an inclusive meaning. For the purpose of this specification, and unless otherwise noted, the term 'comprise' shall have an inclusive

meaning - i.e. that it will be taken to mean an inclusion of not only the listed components it directly references, but also other non-specified components or elements. This rationale will also be used when the term 'comprised' or 'comprising' is used in relation to one or more steps in a method or process.

- 5 It is an object of the present invention to address the foregoing problems or at least to provide the public with a useful choice.

Further aspects and advantages of the present invention will become apparent from the ensuing description which is given by way of example only.

#### **DISCLOSURE OF INVENTION**

- 10 According to one aspect of the present invention there is provided a method for the on farm separation of at least one component from milk

characterised by the steps of

using an automated milking device to extract milk from at least one udder teat of a dairy animal, and

- 15 passing the milk through a separation device to remove said component from the milk.

According to another aspect of the present invention there is provided a method for the on farm separation of at least one component from the milk of a lactating dairy herd,

characterised by the steps of

allowing animals to freely enter a milking shed and be milked by an automated milking

- 20 device, and

passing the milk through a separation device to remove said component from the milk.

The term "component" should be taken to mean any component present in the milk,

such as endogenous milk proteins, fats, enzymes, cells, ions, nucleic acids and so forth.

In one preferred embodiment of the present invention the milk component separated is lactoferrin. However, this is given by way of example only and as such this should be seen as a limitation on the present invention in any way.

5 The term "automated milking device" should be taken to mean any automated or robotic device designed to milk a dairy animal. A range of automated and robotic milking systems are known in the art and could potentially be used in the present invention. For ease of reference throughout the specification, the automated device will herein be referred to as a robotic milking device, though this should not be seen as  
10 a limitation in any way.

The term "milk" should also be taken to include colostrum or milk from late lactation as well as milk from mid lactation or sub-fractions of milk taken during only as part of a milking.

The term "dairy animal" will herein be referred to as a cow. However, this should also  
15 not be seen as a limitation for it is anticipated this method will also be applicable to other milking animals such as goats, sheep and so forth.

The term "separation device" should be taken to mean a device utilising any separation technique known in the art, such as ultrafiltration, chromatographic separation, dialysis and so forth, or a combination of such techniques. Once again, these are given by way  
20 of example only and should not be viewed as limiting in any way. It is anticipated a range of separation techniques could be employed depending on the component of interest and that this would readily be understood by a skilled addressee.

The separation device may be a modular cartridge type unit which incorporates a matrix for removing specific milk components. A number of different cartridges may  
25 be used, whereby milk from a given animal may be passed through a different cartridge

to that of another animal.

In situations where the separation device is able to separate a number of components substantially simultaneously, the elution of the components from the matrix will preferably also isolate the components from each other.

- 5 In some embodiments of the present invention, the milk may be passed through a series of cartridges to remove a number of components from milk.

Once the cartridge has processed a given volume of milk, it can be removed and substituted for a fresh cartridge. The removed unit can then be treated to remove the bound milk components, or stored in a refrigerated unit for subsequent collection  
10 and/or processing.

Preferably once the components have been eluted from the cartridge, the cartridge can be recharged, available for another separation.

In New Zealand, herds are typically milked twice daily in order to obtain maximum milk yields balanced with labour costs. As such, a large volume of milk is collected  
15 from each cow at each milking.

In order to reduce the amount of time taken to milk the entire herd, a large number of individual stalls are often required to allow a number of animals to be milked substantially simultaneously.

Previous on-farm separation methods disclosed by NZ 280724 were able to remove a  
20 number of targeted milk components, but while they worked well in experimental situation, the volume of milk required to be processed during standard twice daily milking presents a number of difficulties.

The separation techniques utilised are limited in both the volume and also the rate at which milk can be processed at any one time. As such, this could result in long delays

during standard twice daily milking, and require large volumes of chromatographic resins to prevent overloading.

In many situations it is thus desirable for components to be separated before milk enters the bulk milk line. The smaller volume of milk needing to be processed ensures  
5 a better degree of component separation in the minimum amount of time, and also reduces the likelihood of the separation device being overloaded.

To be effective however, separation devices thus need to be incorporated into each stall of a milking shed, which at present would make them prohibitively expensive for a standard on-farm situation.

10 The advantage of robotic milking is that cows are milked throughout the day in small numbers, in contrast to the entire herd being milked at substantially the same time. While milking the entire herd together is usually the most time efficient method of milking, it is both labour and resource intensive, not only in the total number of hours worked, but also the time of day the animals must be milked.

15 By using a robotic milking device, cows are able to be milked at any time of the day. A cow is able to freely enter a milking shed a number of times during the day rather than waiting for the twice-daily milking, thus reducing the volume of milk taken from the cow at each milking and thus the amount needing to be processed at any one time.

20 Further, as the whole herd is not being milked at once, only a limited number of stalls and separation devices may be required.

As the milking of the herd is thus staggered throughout the day, there is sufficient time to process each volume of milk and recharge the separation device before the next milking occurs. Alternatively, two or more separation devices could be installed, allowing one device to process a sample while the next animal is milking. As only  
25 small volumes of resin may be required, the cost of such separation techniques become

accessible to on-farm situations.

Further, as an operator is not required to be present at all times, there may be considerable savings in labour costs.

5 Robotic milking also allows individual udder sections to be milked. For example, lactoferrin is known to be produced in high levels in mastitic milk. As such, milk from a mastitic udder quarter could be passed through a separation device to remove the lactoferrin and/or contaminants such as somatic cells or antibiotics, allowing the remaining milk to be diverted back into the main milk flow or alternatively be directed to waste.

10 As small volumes of milk at low flow rates are produced at any one time, more specialised extraction and fractionation systems may be used, improving the quantity and purity of the milk components separated.

15 Robotic milking also allows a mixed herd of cows to be milked at once, whereby milk from cows known to produce high levels of lactoferrin may be processed through a separation device, while the milk from cows with low levels of lactoferrin can be collected direct to the main milk storage vat.

Animals may be identified by usual indicia, or alternatively by way of an electronic identifier or chip.

20 In addition to separating endogenous bioactive components from milk, the method of the present invention will also be able to remove components unacceptable in milk. These include somatic cells, antibiotics, hormones and so forth. Currently if milk is found to be contaminated with these components it is dumped, with the farmer being required to pay substantial penalties.

25 The present invention can also be used to remove endogenous milk components from bovine milk (such as beta-lactoglobulin and lactose) to make such milk acceptable to

consumers with allergies to dairy products.

Another application of the present invention includes the processing of milk from transgenic animals which produce a specific protein in their milk. As the protein of interest is known, a specific separation device or protocol could be designed to isolate  
5 the protein of interest, without altering the standard milk composition.

Early removal of bioactive milk components minimises the degradation of these components and any loss of activity that usually occurs during standard milk processing procedures. Further, immediately isolating the compounds of interest reduces the amount of time the components may be subjected to enzymatic or  
10 microbial degradation whilst being stored.

The present invention has sought ways to improve the on-farm separation of milk components by utilising automated milking technology.

#### **BRIEF DESCRIPTION OF DRAWINGS**

Further aspects of the present invention will become apparent from the following  
15 description which is given by way of example only and with reference to the accompanying drawings in which:

Figure 1 shows a diagrammatic layout of milk flow into and out of a robotic milking stall in accordance with one preferred embodiment of the present invention;

20 Figure 2 shows a diagrammatic layout of milk flow in accordance with another preferred embodiment of the present invention; and

Figure 3 shows a diagrammatic layout of milk flow in accordance with a third preferred embodiment of the present invention.

## BEST MODES FOR CARRYING OUT THE INVENTION

Figure 1 shows the milk-flow into and out of a robotic milking stall (1). The milk is transferred from the cow (not shown) to a holding vessel (2), then either pumped out of the holding vessel (2) through to the separation device (3) or bypassed (4) around the separation device (3). Then, the milk is transferred to a bulk holding tank (5), whilst the separated fraction is retained at the separation device (3).

Figure 2 shows a schematic layout of a robotic milking stall (1) with two collection (2a and 2b) and separation devices (3a and 3b), whereby one device (2a and 3a) can be operating whilst the second (2b and 3b) is collecting milk from the next animal. This would be in the interest of higher throughput. Alternatively, each device could place the first milk from one animal into one collection/separation unit (2a and 3a) and then later milk portions from the same animal into the other (2b and 3b). This could be useful for components that are higher in the later portions, such as lactoferrin. Alternatively, this device could place milk from one or more udder teats into different collection/separation units. This could be useful for components that are higher in one quarter, such as a quarter having mastitis and, therefore, higher immunoglobulins.

Another variation on Figure 1 could be multiple separation devices (3), useful for separating multiple components from the same animal's milk, as shown by Figure 3.


Aspects of the present invention have been described by way of example only and it should be appreciated that modifications and additions may be made thereto without departing from the scope thereof.

Intellectual Property  
Office of NZ


20 DEC 2002

RECEIVED

SENSORTEC LIMITED  
by their Attorneys

  
JAMES & WELLS

**Figure 1**



**Figure 2**





Figure 3



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**